



16mm connector with 6 or 8 pins

Single Ended Outputs

6-Pin Connector*	Function	Wire Color
1	Common	Black
2	+vdc	Red
3	Output Z	Brown
4	Output A	White
5	Output B	Green
6	not used	-

* connector is Amphenol T3402000 or equivalent

Differential Line Driver Outputs

8-Pin Connector*	Function	Wire Color
1	Output +A	White
2	Output +B	Green
3	Output +Z	Yellow
4	Supply voltage	Red
5	Common	Black
6	Output -A	Blue or Green
7	Output -B	Brown
8	Output -Z	Orange

* connector is Amphenol T3506000 or equivalent

See the RH datasheet for more information

Rev	Description	Date	This information is approved only if it is stamped "APPROVED", signed, and dated.	Tolerances	MI98: RH encoder with I6mm connector		
			This document is provided for a specific purpose and the disclosed information remains our property. It may not be disclosed, copied, or reproduced, except for the specific purpose, without Photocraft's prior approval. This notice must appear on any copy or reproduction of this document.	.XXXX ± .0005 .XXX ± .005 .XX ± .01 .X ± .015 Fractions ± 1/32 Angles ± 15 min Runout ± .003	By: TRD	Mat'l:	
			© 2007, Photocraft Inc.	Unless otherwise specified	Orig. Date: 6/12/08	Finish:	Scale: 1 : 1.33
					Photocraft Inc 602 E. North Street, Elburn IL 60119, USA www.photocraftencoders.com		8AI98