


Shown with optional  
20cm circumference measuring wheels  
and 16mm connector

## FEATURES

- Generates pulses for accurate linear measurement
- Selectable resolution: Millimeters per Pulse
- Heavy Duty construction
- Compact size
- Precision 20cm circumference measuring wheel
- 16mm or M12 connector, or attached cable
- Enhanced "Anti-Jitter" feature for web applications
- ESD, Short Circuit, Reverse Voltage protection
- Various mounting hardware kits are available
- Other programmable models are available

## DIMENSIONS

(shown with optional 16mm connector)



PO Box 25135 813-886-4000  
Tampa FL 33622-5135, USA 800-237-0946  
ttco.com • photocraftencoders.com

## SPECIFICATIONS

### Mechanical

**Maximum Speed:** 3,000 rpm

**Shaft Loading:**

- Radial: 40 lbs. / 18.1 kg
- Axial: 30 lbs. / 13.6 kg

**Bearing Life:** 32 x 1,000,000/rpm = hours

**Materials:** Switch cover: ABS

- Case: Aluminum, anodized
- Shaft: 303 Stainless steel

**Weight:** 12 oz. / 340 grams (without accessories)

**Protection:** IP50 is standard, IP66 available

### Electrical Connections

Function	Connectors			Wire Color
	16mm 6-Pin	16mm 8-Pin	M12 4-Pin	
Common +vdc	1	5	3	Black
Output A	2	4	1	Red
Output -A	4	1	4	White
	-	6	2	Green

Unlisted pins are not used.

16mm 6-pin is Amphenol T3402000 or equivalent, for Single Ended outputs.


16mm 8-pin is Amphenol T3506000 or equivalent, for Differential Line Driver.

M12 4-pin is Turck FS4.4/.. or equivalent for either Single or Differential Outputs.

Attached cable is 10-ft / 3-meters. Other lengths are available.

### Configuration Switches

Determines the linear movement per output pulse when used with the 20 centimeter circumference measuring wheel (MW-20).



Pulse Selection Not Used

Millimeters per Pulse											
1	2	3	4	5	10	25	50	75	100	125	150
1	2	3	4	5	10	25	50	75	100	125	150
1	2	3	4	5	10	25	50	75	100	125	150
1	2	3	4	5	10	25	50	75	100	125	150
1	2	3	4	5	10	25	50	75	100	125	150
1	2	3	4	5	10	25	50	75	100	125	150

Switch definitions: ☐ Up (off), ☒ Down (on).

### Electrical

**Supply Voltages:** (specify when ordering)

5 VDC or 8-30 VDC

**Current:** 50 mA max (no load)

100 mA max (line driver)

**Pulse Rate:** 0 - 30 kHz

**Pulses per Revolution:** 2, 2-2/3, 4, 8, 10

13-1/3, 20, 40, 50, 66-2/3, 100, 200

**Operating Temperature:** -25° to +85° C

**Output Circuit:** (specify when ordering)

Single Ended:

- 7273 open collector (30 VDC max, 50 mA max)
- 7272 Push-Pull (50 mA max source or sink)

Differential Line Driver:

- 7272 differential line driver (output level same as supply voltage)
- RS422 differential line driver (with regulated 5vdc output level)

**Output Waveshape:**

Square wave output A is 50/50 duty cycle nominal. Output -A is the compliment of A.

- Pulse symmetry: 180°±30%
- Pulse interval jitter: 30% max

**Enhanced Anti-jitter:** Developed for conveyor applications that typically operate in one direction, and do not want pulses generated if the conveyor stops or reverses for a short distance. Pulses are generated as long as rotation continues in one direction. If the direction reverses then pulse output ceases until it returns to its original direction and position it was at before reversing. If the reverse rotation exceeds 10 rotations then the encoder resets assuming the current direction is forward and begins pulsing.

### Accessories

See our website or contact us for more information about cables, measuring wheels, and mounting hardware.

## MODEL NUMBER

R21	P20EAJ						
Model Number	Program Name: Call or see our website for information about other programs.	Supply Voltage: 5 or 8-30	Output Circuit: leave blank for 7272 Push/Pull, C=7273 open collector, DH=line driver, DL=RS422 line driver	Cable/Connector: leave blank for attached cable, S=16mm connector, S3=M12 connector	Modification Number: optional modification or special feature ID. Call or see our website.	Accessories: leave blank for no accessories. Call or see our website for more information.	

Example: R21-P20EAJ/8-30S MW20-3M R21 with P20EAJ program, 8-30 vdc, 7272 push/pull output, 16mm connector (6-pin), and Accessories: MW-20 wheel, 3 meter cable